



QCX150-A



QC150-B



QC50-A

QC50-B



NEW

QCY90-A

QC90-B

| | QC50 | QC90 | QC150 | QC160 | QC200 |
|--|---|------------------|--------------------|--------------------|--------------------|
| 介质 Medium | 已过滤, 润滑型 / 未润滑型压缩空气 Filtered, lubricated / non lubricated compressed air | | | | |
| 压力范围 Pressure range | -1 + 6 bar | | | | |
| 温度范围 Temperature range | 5 + 60 °C | | | | |
| 机械手侧快的速转换模块 Robot side quick changer | 103 g QC50-A | 318 g QC90-A | 1123 g QC150-A | 1200 g QC160-A | 2640 g QC200-A |
| 机械手侧带安全阀的快速转换模块 Robot side quick changer with safety valve | - | 595 g QCX90-A | 2200 g QCX150-A | 2200 g QCX160-A | 4900 g QCX200-A |
| 机械手侧带自动阀的快速转换模块 Robot side quick changer with automatic valve | - | 350 g QCY90-A | - | - | - |
| 治具侧的快速转换模块 Gripper side quick changer | 65 g QC50-B | 227 g QC90-B | 827 g QC150-B | 900 g QC160-B | 1890 g QC200-B |
| | | | | | |
| | | | | | |
| | | | | | |